

YP20T



Blue
\$1,099 MSRP*

TOP FEATURES

1. The YP20T uses a 175cc, OHV 4-stroke engine that is quieter, more powerful, and consumes less fuel than comparable engines.
2. It has a powerful pump, pumping up to 184 gal/min (11,040 gal/hr) through a two-inch port.
3. Delivers a 92-foot total head, with a 26-foot suction head.
4. Can handle solids up to .79" (20 mm).
5. Durable Pump - Impeller and volute case are cast iron for greater strength and durability; and they withstand wear from grit, sand, silt, etc.
6. Outstanding Seal Durability - Newly adopted Japanese-made silicone carbide (SiC) seal - has better durability compared to conventional carbon ceramic seals.
7. 2-inch Standard National Pipe Thread (NPT) fittings connect easily with the suction and discharge hoses.
8. 3 year industrial and residential warranty with optional Y.E.S. for customer peace of mind.



*Manufacturer's Suggested Retail Price (MSRP) shown. Does not include tax, title, prep or destination charges. Actual prices set by dealer.

FEATURES & BENEFITS

FEATURES

DeWatering Applications - Use for these types of DeWatering applications: Job site excavations, Utility vaults, Motocross tracks, Mining sites, Lakes and ponds and Barge holds.

Powerful Pump - Pumps up to 184 gal/min (11,040 gal/hr). Use for moving massive amounts of water.

Cast iron cylinder lining has optimal heat dissipation — Cast iron cylinder lining has optimal heat dissipation.

Automatic oil warning system shuts off engine before oil level is low — Prevents engine damage, avoids costly repairs, minimizes down time, enhances long term durability.

Transistorized ignition provides lean, efficient spark — Maintenance-free and ensures fast, easy starting, reliable operation.

Auto-decompression — Automatically “opens” exhaust valve to reduce compression for easier starting.

EPA Emission Engine Life Rating — The YP20T meets the strictest environmental standards - EPA and CARB.

Tool and Strainer Kit - Standard equipment.

yamahamotorsports.com
For Accessories, visit shopyamaha.com

SPECIFICATIONS:

Pump Type	Self-priming, Centrifugal
Suction Port	2 in
Discharge Port	2 in
Discharge Capacity	184 gal / min
Self Priming Time	100 sec / 26.25 ft
Total Head Lift	92 ft
Suction Head Lift	26 ft
Solids Handling (Max)	.79 in (20mm)
Engine	MZ 175 4-stroke,OHV, Forced air cooled
Fuel	Unleaded Gasoline
Fuel Capacity	1.06 gal
Starting Method	Recoil Starter
Dry Weight	105 lb
L x W x H	26.18 x 18.19 x 20.31 in
Limited Warranty	3 years
Color	Blue